

TECHNICAL DATA SHEET-SDS





1. Identification Of Substance

Product Details

Product Name:

Polyaspartic polyurea resin

Products Use:

Aggregate floor, flake floor, quartz, marble, granite floor and stone floor
floor potting, coating, insulation, carbon fiber products

/Supplier By:

GRAVITY

Agios Nikolaos Jct, Limassol 3105

Tel& Emergency Tel:+35797881886

2. Hazards Identification

Emergency Overview:

Since it is Eco-Friendly it has Zero-VOC

Not a hazardous substance or mixture according to
Regulation (EC) No.1272/2008.

Not a hazardous substance or mixture according to
EC-directives 67/548/EEC or 19999/45/EC

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
as amended by Regulation (EU) 2020/878

GHS Classification:

The products does not need to be labelled in accordance
with EC directives or respective national laws.

Other hazards:

This substance/mixture contains no components
considered to be either persistent, bioaccumulative and
toxic (PBT), or very persistent and very
bioaccumulative(vPvB) at levels of 0.1% or higher.

Potential Acute Health Effects

Eyes:

Mildly irritating to eyes.

Skin:

Prolonged or repeated skin contact can cause irritation.

Inhalation:

May be irritating to upper respiratory tract.

Ingestion:

Single does oral toxicity is considered to be extremely
low. No hazards expected from swallowing small
amounts incidental to normal handling
operations. Ingestion may cause gastrointestinal
irritation.

3. Standard concrete substrate conditions

Certificates - Tested and compliant

- Strength: S-C20/+25.
- Humidity: W ≤ 5%.
- Temperature: 0-35 oC.
- Relative humidity: ≤ 85%.

- CE EN-13813:2002 *
- US FDA 21 CFR 175.300
- RoHS Directive (EU)2015/863 AnnexII

* Property: Standard / Value
Classification: EN-13813:2002
Bond Strength: Meets or exceeds S-C20/+25 requirements
Chemical Resistance: Compliant with EN-13813 for resin screeds
Application: Temperature 0°C to 35°C



4. First aid Measures

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Inhalation:

Remove person to fresh air. Get medical attention.

Ingestion:

Seek medical attention.

5. Fire Fighting Measures

Fire Fighting Media: This products is non flammable,if fire caused use like alcohol cleaner,please use Dry chemical, carbon dioxide, alcohol foam and water fog

Special Fire-Fighting Procedures:

As in any fire, firefighters should wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH(approved or equivalent),and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and procedures :

Evacuate area. Keep away from heat/sparks/ open flames/hot surface.- Use only non-sparking tools because of plastic bucket. Ventilate with fresh air. Refer to other section of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

Environmental precautions:

Methods material for Containment and cleaning up:

Avoid release to the environment If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Cover spill area with a fire-extinguishing foam. An appropriate aqueous film forming foam(AFFF) is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material .does not remove a toxic, corrosivity or



commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by a appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Collect the resulting residue containing solution. Seal the container. Dispose of collected material as soon as possible.

7. Handling And Storage

Precautions for safe handling:

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surface.-No smoking. Do not spray on an open flame or other ignition source. Pressurized container :Do not pierce or burn ,even after use .Do not breathe/dust/fume/gas/mist/vapours/spray Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment(eg. gloves, respirators) as required. Vapours may travel long distances along the ground or floor to an ignition source and flash back. Do not use in a confined area or areas with or no air movement.

Conditions for safe storage including any incompatibilities:

Protect from sunlight. Do not expose to temperatures exceeding 50°C / 122F. Store in a well-ventilated place. Keep



container tightly closed. Store away from acids. Store away from oxidising agents.

8.Exposure Controls And Personal Protection

Engineering controls:	Do not remain in area where available
	oxygen maybe reduced. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/spray. If ventilation is not adequate, use respiratory protection equipment.
Personal Protection Eyes:	Wear safety glasses with side shields. Wear additional eye protection such as chemical goggles or face shield if splashing or spraying hazard exists. Have an eye wash station available.
Body:	To prevent skin contact use coveralls, apron, boots, or lab coat.
Hands:	Avoid skin contact by using chemically resistant gloves.
Respiratory:	No respiratory protection required under normal conditions of use. Use local exhaust to control excessive vapors/mists. If excessive vapors or mists are persist use appropriate NIOSH/MSHA approved organic vapor/mist respirator.
Other:	Open wounds or skin surface disruptions should be covered with a chemical resistant patch to minimize absorption risks. Clean clothing should be worn daily to avoid possible long-term build up of the product leading to chronic overexposure.

9.Physical And Chemical Properties

General Information

Form:	Liquid
Color:	Transparent
Odor:	Slight amine smell



Flash point:	446F 230°C
Density:	1.02-1.10g/cm
Viscosity:	30cps-40000cps/25°C

10. Safety Instruction

Always wear protective gloves and glasses and avoid contact. May cause allergy. If the material comes in touch with your eye add a lot of water without touching. And get in touch with your doctor and seek medical advice. The content is not flamable but keep away from heat/flames/sparks/hot surfaces because the bucket is plastic

11. Transport Information

ADR/RID: Not dangerous goods
IMDG: Not dangerous goods
IATA: Not dangerous goods

12. Regulations

Product related hazards information: Observe the general safety regulations when handling chemicals.

National regulations: All components of this product are listed in the EU Environmental Protection Agency Toxic Substances Control Act Chemical substance Inventory.

Information about limitation of

Use: For use only by technically qualified individuals.

STORAGE

12 months from production date, stored in original unopened packaging protected from direct sun exposure and frost. Storage temperature 0°C - 35°C.

TECHNICAL CHARACTERISTICS

Application temperature +0°C until +35°C. Temperature resistance -40°C until 120°C.
Humidity ≤85% (RH) . Flooring drying time 8-12h (after 24h you can step on it)
Parking drying time 24h, then need a top coat with roll with the same material without the quartz (after 5 days you can park on it)



Address: Riga Fereou & Andrea Zakou
Christina Center 1st Floor, Office 101, 3095,
Limassol - Cyprus

@gravity.resin.quartz

Gravity.services.cy@gmail.com

+357 97 881 886

WWW.GRAVITYRESINQUARTZ.COM