

GRAVITY SEALER

TECHNICAL DATA SHEET



GRAVITY SEALER

DESCRIPTION

High-Performance GRAVITY SEALER with UV Resistance and Enhanced Durability. For use on resin quartz, marble, granite, and natural stone carpet systems.

APPLICATION PROCEDURE

For use after any Gravity Resin Quartz system

The material must not come into contact with water until it is fully dry. Ensure that all tools are clean before and during application.

Applying the GRAVITY SEALER: apply evenly using a rubber squeegee or paint brush.

FOR EXTERIOR USE: Allow the surface to dry for 24 hours after application. For exterior applications, use Gravity Resin Quartz Floor Bucket A+B (mixed) as a top coat, applied with a paint roller. (Make sure the material is evenly distributed across the roller. Before applying to the surface, roll it a few times to remove excess material and ensure a thin, even coat.). After applying the top coat, allow a further 24 hours for curing.

FOR INTERIOR USE: No top coat is required. Allow 24 hours for curing.

STORAGE

12 months from production date, stored in original unopened packaging protected from direct sun exposure and frost. Storage temperature 0°C - 35°C.

TECHNICAL CHARACTERISTICS

Application temperature: 0°C to +35°C
Temperature resistance: -20°C to +90°C
Relative humidity: ≤85% RH
Drying time: 24 hours

SAFETY INSTRUCTIONS

Always wear protective gloves and safety glasses. Avoid contact with skin and eyes. May cause an allergic reaction. If the material comes into contact with the eyes, rinse cautiously with plenty of water. Avoid rubbing the eyes. Seek medical advice if irritation or other symptoms persist. The contents is not flammable but keep away from heat/flames/sparks/hot surfaces because the bucket is plastic.

POISON CENTER 1401

Technical Property	Typical Value
Appearance	Transparent to slightly translucent solid film
Odour	Slight, mild almond-like scent
Boiling Point	Approx. 100°C
Water Solubility	Fully miscible with water
pH	7.5-8.5
Storage	Store below 50°C in a cool, dry, ventilated area
Application Temp.	+0°C until +35°C
Temp. Resistance	-20°C until 90°C Humidity ≤85% (RH)
Dry Time	24h





Address: Riga Fereou & Andrea Zakou
Christina Center 1st Floor, Office 101, 3095,
Limassol - Cyprus

    @gravity.resin.quartz

 Gravity.services.cy@gmail.com

  +357 97 881 886

WWW.GRAVITYRESINQUARTZ.COM